

## ABC DRY POWDER MAP-50% (STORED PRESSURE) 6 KG FIRE EXTINGUISHER

**KANEX ABC Dry Powder MAP-50% (Stored Pressure) 6 kg Fire Extinguishers** applicable on Class A, B, C and electrically started fires.

**Brief description:** ABC Dry Powder MAP-50% Fire Extinguishers with nominal charge of 6 kg (+/-2%). Constructed of MS Sheet by MIG Welding process and brass forged discharge Valve.

**Approved Fire ratings** 3A:21B with an effective throw of about 5 meters (Min. 2 m.) and discharge about 94% (Min. 85%).



Client :

PO No.

### 1.00 GENERAL DATA

1.01	Manufacturer	Kanadia Fyr Fyter Pvt Ltd
1.02	Trade Mark	"KANEX"
1.03	Standard Code	IS 15683:2006
1.04	Type	Portable Stored Pressure
1.05	Quantity	

### 2.00 MATERIALS OF CONSTRUCTION

2.01	Extinguishing Medium	Mono Ammonium Phosphate based dry powder 50% (Confirms to IS 14609)
2.02	Body	Mild Steel Sheet having Max. of 0.25% <b>C</b> , 0.05% <b>P</b> and 0.05% <b>S</b>
2.03	Neck Ring	M.S. Pipe
2.04	Valve	Brass
2.05	Siphon Tube	Plastic
2.06	Pressure Gauge/indicator	As per IS 15683:2006
2.07	Wall mounting Bracket with screw	Mild steel (Powder Coated)
2.08	Discharge Hose with Nozzle	Rubber Braided EPDM Hose (Length:465mm) With Plastic Nozzle

### 3.00 GUARANTEED PERFORMANCE

3.01	Performance Requirement	<b>Min. effective Discharge Time:</b> 13 Sec. (Actual : 24 Sec. approx) <b>Bulk Range of Discharge:</b> Min. 2 meter (Actual : 5 meter approx) <b>Percentage of Discharge:</b> Not Less than 85 % (Actual : 94% approx)
3.02	Fire Rating	3A:21B
3.03	Temperature Range	-30 °C to +55 °C
3.04	Service Pressure	15 bar
3.05	Maximum Service Pressure	18 bar

### 4.00 ROUTINE TESTS

4.01	Pressure test (Pt)	35 bar (3.5 MPa)
4.02	Minimum Burst Pressure test (Pb) for Body	55 bar (5.5 MPa)
4.03	Leakage test	By applying soap solution leakage to checked
4.04	Partial discharge	The second pressure or weight shall not be less than 75% of the first after interruption of the Discharge.
4.05	Burst Pressure Test For Discharge Hose	Not Less than 35 bar (3.5 MPa)

### 5.00 TYPE TESTS

As per IS 15683

### 6.00 DIMENSIONS

		<b>Max. Diameter:</b> 150±10 mm. <b>Height:</b> 530 mm (Approx.)
6.01	Thickness of sheet	Made Up of 1.8 mm
6.02	Full weight of cylinder	9.3 kg (Approx)
		Phosphate Treatment Followed by epoxy powder coating of body DFT Not less than 50 Micron

### 7.00 ANTI - CORROSIVE TREATMENT

### 8.00 ACCESSORIES (BRACKETS & SCREWS)

Provided

### 9.00 MISCELLANEOUS

9.01	Inspection & Testing	As per approved GTP
9.02	Finish	PO Red as per IS : 5 (Shade 538 )
9.03	Marking	As per IS 15683:2006
9.04	Approvals	BIS
9.05	Maintenance, Care and Refilling	As per IS:2190

### 10.00 Packing

Corrugated boxes (Outer box sizes: 360x170x570mm)